



**LALIZAS**   
*Simply life saving*

[www.lalizas.com](http://www.lalizas.com)

**LIFEBUOY RING**  
**+ ACCESSORIES**

# Behold

The new Height Champion

800m



0098

For use on big ships and offshore drilling units\* with lifebuoy drop storage height up to 80m

\* Certified in accordance with the IMO MODU Code



# Behold

The new Height Class

## **LALIZAS** **Lifebuoy Ring SOLAS**

Designed for pleasure & commercial usage.  
Features an orange polyethylene outer shell that  
does not deteriorate. Remains unaffected by extreme  
weather conditions. Flame & Oil Resistant.

Code **70090** : **2,5 kg** (5.11 lb)

Code **70110** : **4,0 kg** (8.81 lb)



0098

**For use on big ships & IMO MODU certified  
offshore drilling units\*\* with lifebuoy  
drop storage height up to**

# 80m

### **CE Approved**

According to SOLAS

L.S.A. Code by G.L.Hamburg ©

CE approval certificates replace all the  
National approval certificates of European  
committee member states (D.O.T-U.K etc).

\*\* IMO L.S.A Code (Life-Saving-Appliances Code) as amended, corresponds to the latest  
amendment of chapter III of SOLAS in force since June 1998, as well as the Maritime Equipment Directive 96/98/EC.

\*\* Suitable for offshore drilling units certified in accordance with IMO MODU Code. IMO MODU Code corresponds to the code for construction & equipment  
of "MOBILE OFFSHORE DRILLING UNITS".

## **LALIZAS** *Simply life saving*

# Behold

The new Height Champion



0098

SUITABLE FOR  
OFFSHORE DRILLING  
UNITS, CERTIFIED IN  
ACCORDANCE  
WITH THE IMO  
MODU CODE

**U.V.  
PROTECTED  
OUTER SHELL**

## *Main Specifications*

- \* Drop Height: **80m**
- \* Strength Resistant: **90kg Test**
- \* Storage Temperature: **-30° C till + 65° C**
- \* Floatable/Unsinkable: **14.5kg Test**
- \* Flame / Diesel Oil Resistant
- \* PE Lifebuoy Shell

The PE Grab line which surrounds the LALIZAS Lifebuoy Ring, is designed to withstand oil and flames and provides easy & quick grab in case of emergency

Every LALIZAS Lifebuoy Ring is equipped with 400 sq.cm of Lalizas approved Retro-Reflective Tape (LALIZAS Code 70180)

The Highly visible colour of LALIZAS Lifebuoy Ring makes it easily detectable in water, through waves and humidity

**LALIZAS**   
Simply life saving

# Behold

## The new Height Champion

### **LALIZAS Lifebuoy Ring SOLAS**

Being on top of safety standards in marine equipment industry, requires tremendous effort & true passion... Two elements which enforce our originality & challenge us with every day.

**LALIZAS Lifebouoy Ring SOLAS is the new 80m height Champion.**



#### COMPARISON BOARD

LALIZAS Code	LALIZAS Lifebuoy Ring SOLAS 2,5kg <sup>®</sup> LALIZAS Code	LALIZAS Lifebuoy Ring SOLAS 4,0kg <sup>®</sup> LALIZAS Code
PRODUCT CERTIFICATES	MED approved according to SOLAS 74/78 as amended Reg. III/4, III/7, III/34, X/3, MSC.48(66), MSC.81(70) [LSA Code] as amended by MSC.207(81), MSC.36(63) and MSC.97(73) [HSC Code].	
WEIGHT	2.5 kg (5.11 lb)	4.0 kg (8.81 lb)
DROP HEIGHT	80m	80m
LIFEBUOY SHELL / INTERNAL MATERIAL	PE / PU Frothing	PE / PU Frothing
GRAB LINE MATERIAL	PE	PE
REFLECTIVE TAPE	Lalizas LA70180, SOLAS/MED approved Retro- Reflective Material. In compliance with resolution A.658 (16)	
HIGHLY VISIBLE COLOUR	YES	YES
STORAGE TEMPERATURE	-30° C up to + 65° C	-30° C up to + 65° C
RESISTANT TO FLAME / DIESEL OIL	YES / YES	YES / YES
TESTED FOR OPERATION w. LIGHT & SMOKE SIGNAL	-	YES
EXTERNAL/INTERNAL DIAMETER	715mm ± 5 / 445mm ± 5	715mm ± 5 / 445mm ± 5

**LALIZAS**   
Simply life saving

# Behold

new Height Champi



0098



**COMBINE**  
**LALIZAS Lifebuoy Ring SOLAS**  
**WITH...**



Code 98992  
**LALIZAS Floating Rope, Diam. 8mm®**

Code 70260  
**LALIZAS Floating Rope Diam. 8mm, L 30m®**



Code.....71326  
**LALIZAS Lifebuoy Light**  
**SOLAS/MED-ATEX/IECEX**



Code 70030  
**LALIZAS Lifebuoy Light M.O.B (LSA code)®**

Code 70000  
**LALIZAS Lifebuoy light holder®**



Code.....71325  
**LALIZAS Lifebuoy Light**  
**SOLAS/MED**

**LALIZAS**   
*Simply life saving*

