



Packing Imballo

Weight with box (EXTREME 2D 1,5HP) :
51 Kg - 112,4 Lbs
Box dimensions cm : 60 x 45 x 86 (0,23 m³)
Quantity per (110x110) PALLET : 8 pc.

EXTREME 2V



 Dental unit	Pneumatic		
	Electric-Pneumatic		
	Electric		
EXTREME 0,75 CV	1	X	X
EXTREME 1,50 CV	2	1	1
EXTREME 2,00 CV	2	2	1
EXTREME 2,50 CV	4	3	2
EXTREME 3,00 CV	6	4	3

Compressor Model	Tank	Dryer	Cylinders	Air Intake	Air delivery	Pressure	Power	Phase	Noise	Weight	Dimensions
Modello Compressore	Serb.	Essicat.	Cilindri	Aria Aspirata	Aria resa	Pressione	Motore	Fase	Rumore	Peso	Dimensioni
Type	Liters	Complete	N°	l/min. - C.F.M.	l/min. - C.F.M.	Bar - Psi	HP - kW	Type	dB	Kg - Lbs	cm (LxWxH)
EXTREME 2V 50L 0,75	50	X	2	200 - 7,0	60 - 2,1 (5 BAR) 42 - 1,5 (8 BAR)	8 - 114	0,75 - 0,5	Single	72	36,5 - 81	46 x 43 x 83
EXTREME 2D 50L 0,75	50	✓	2	200 - 7,0	60 - 2,1 (5 BAR) 42 - 1,5 (8 BAR)	8 - 114	0,75 - 0,5	Single	72	45 - 99	58,5 x 43 x 83
EXTREME 2V 50L 1,50	50	X	2	240 - 8,5	125 - 4,4 (5 BAR) 100 - 3,5 (8 BAR)	8 - 114	1,50 - 1,1	Single	72	39,5 - 87	46 x 43 x 83
EXTREME 2D 50L 1,50	50	✓	2	240 - 8,5	125 - 4,4 (5 BAR) 100 - 3,5 (8 BAR)	8 - 114	1,50 - 1,1	Single	72	48 - 106	58,5 x 43 x 83
EXTREME 2V 50L 2,00	50	X	2	350 - 12,4	156 - 5,5 (5 BAR) 127 - 4,5 (8 BAR)	8 - 114	2,00 - 1,5	Single	73	42,5 - 94	46 x 43 x 83
EXTREME 2D 50L 2,00	50	✓	2	350 - 12,4	156 - 5,5 (5 BAR) 127 - 4,5 (8 BAR)	8 - 114	2,00 - 1,5	Single	73	51 - 112	58,5 x 43 x 83
EXTREME 2V 50L 2,50	50	X	4	480 - 17,0	240 - 8,5 (5 BAR) 190 - 6,7 (8 BAR)	8 - 114	2,50 - 1,84	Single	73	52 - 115	64 x 45 x 89
EXTREME 2D 50L 2,50	50	✓	4	480 - 17,0	240 - 8,5 (5 BAR) 190 - 6,7 (8 BAR)	8 - 114	2,50 - 1,84	Single	73	60 - 132	64 x 45 x 89
EXTREME 2V 50L 3,00	50	X	4	600 - 21,2	312 - 11 (5 BAR) 250 - 8,8 (8 BAR)	10 - 145	3,00 - 2,2	Three	73	54 - 119	64 x 45 x 89
EXTREME 2D 50L 3,00	50	✓	4	600 - 21,2	312 - 11 (5 BAR) 250 - 8,8 (8 BAR)	10 - 145	3,00 - 2,2	Three + N	73	62 - 136	64 x 45 x 89

With automatic thermal protection

Con protezione termica automatica